

SMART INDUCTOR 5000 CLASSIC



- Induction heater for fast and simple removal operations of vehicle parts. Supplied with Super Remover, Heat Twister, Pad Inductor accessories, 3 levers and remote control.
- Intelligent and fully automatic intensity adjustment (Smart Power) using an innovative AutoCheck micro-processor system.
- Digital, user friendly panel.
- Automatic and manual mode.

DESCRIPTION

Induction heating system that is an intelligent solution for speeding up and simplifying the removal of glued (windows, rear windows, plastic parts, stickers, glass roofs, interior and exterior trims, etc.) or blocked (bolts, bearings, gears, etc.) parts from vehicles.

It is particularly suitable for vehicle bodies, and guarantees greatly reduced intervention times.

It adjusts its intensity in an intelligent and completely automatic manner (Smart Power) using an innovative AutoCheck microprocessor system.

Using the principle of electromagnetic induction, it can transfer a large amount of heat to a specific area (Smart Protection) in just a few seconds. In this way it does not damage glass, rubber, plastic and painted surfaces in the area being worked on, or even in the surrounding areas.

For maximum practicality and operator safety, it activates automatically (Smart Activation) near the area in which it has to work.







Features:

- intelligent control with Autocheck system;
- user-friendly digital panel;
- automatic and manual mode;
- activation and correct operation signals;
- foot control.

Supplied complete with accessories: Super Remover, Heat Twister, Pad Inductor and 3 levers.



TECHNICAL DATA

 CODE	CODE 865011	 V_{1PH}	SINGLEPHASE MAINS VOLTAGE 200 - 240 V	 F	MAINS FREQUENCY 50 / 60 Hz
 P_{MAX}	MAX ABSORBED POWER 2,4 kW	 F	HEATING FREQUENCY 35 - 100 kHz	 P	MAX HEATING POWER 2,3 kW



PROTECTION DEGREE
IP21



DIMENSIONS (LxWxH)
39 x 26 x 23 cm



WEIGHT
10,4 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL