

## Blind rivet adapter **BR20**

Item no. 700100

**PATENTED**

SWIVEL JOINT

Our **smallest pulling adapter** for the global market!

**Traction force 20 kN**

- freely tiltable and rotatable
- for rivets with shaft: Ø 2.0-4.2 mm
- extremely good accessibility for challenging riveting tasks

| Dimensions         | Stroke | Weight | F max. | Swivel angle | interlock steps |
|--------------------|--------|--------|--------|--------------|-----------------|
| 100 × 56 × 74.5 mm | 22 mm  | 1.0 kg | 20 kN  | 120°         | 30°             |



incl. mouthpieces

## Blind rivet adapter **BR50**

Item no. 700101

**PATENTED**

SWIVEL JOINT

The power package designed for the future!

**Traction force 50 kN**

- freely tiltable and rotatable
- for rivets with shaft: Ø 2.0-5.0 mm
- extremely good accessibility for challenging riveting tasks

| Dimensions  | Stroke | Weight | F max. | Swivel angle | interlock steps |
|-------------|--------|--------|--------|--------------|-----------------|
| 252 × 56 mm | 25 mm  | 1.5 kg | 50 kN  | 120°         | 30°             |



incl. mouthpieces

## Blind rivet adapter **BR80**

Item no. 700112

**PATENTED**

SWIVEL JOINT

The universal pull cylinder for multiple applications!

**Traction force kN**

- ultra high strength blind rivets and nuts
- HUK Born
- studs
- bolts
- Magna Grip



| Dimensions   | Stroke | Weight | F max. | Swivel angle | interlock steps |
|--------------|--------|--------|--------|--------------|-----------------|
| 200 × 112 mm | 25 mm  | 2.5 kg | 80 kN  | 120°         | 30°             |



SELECT THE MATCHING ADAPTER  
ACCORDING TO YOUR NEEDS

## Extensions & pulling adapters for BR50/BR 80

|          | Extensions   |              | Pulling adapters |              |              |              |
|----------|--------------|--------------|------------------|--------------|--------------|--------------|
| Item no. | 700150       | 700151       | 700138           | 700139       | 700136       | 700137       |
| Name     | BR 50        | BR 50        | BR 50            | BR 50        | BR 80        | BR 80        |
| Length   | 100 mm       | 150 mm       | 55 mm            | 55 mm        | 65 mm        | 65 mm        |
| Ø        | 2.0 - 5.0 mm | 2.0 - 5.0 mm | 3.0 - 5.5 mm     | 5.5 - 7.0 mm | 3.0 - 5.5 mm | 5.5 - 7.0 mm |

**NEW**

