

## Accessories

Item no.	808021	808022	808023	808027	808028
Name	Quick connect valve for gas bottle	Pressure regulator valve Cylinder connection & Hose connection R3/8" li	Pressure regulator valve Cylinder connection DIN Combi Hose connection R3/8" li	Refill adapter DIN Combi  Connection: DIN Combi M14 x 1.5	excess flow cut-off valve  Connection: R3/8" x R3/8" li
VE	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.

Pressure regulator with fixed working pressure of 2 bar.  
Maximum flow rate is 6 kg/h.



## High pressure hose

Item no. 808025

High pressure hose according to DIN 4812 made of rubber with textile insert.  
The special rubber compound is frost-resistant and thus allows work down to -30 °C.  
For all soldering work up to a working pressure of 2 bar.  
Pre-assembled with hose connections R3/8" le.



## WS Tinning set

Item no. 812005

The complete set for tinning.  
Bar tin - 25% lead content

Scope of delivery:

- 1 x Power Jet with cyclone burner
- 1 x gas bottle empty (f. propane or butane)
- 1 x refill adapter
- 1 x Solder paddle | oiled | round
- 1 x Solder paddle | oiled | narrow
- 1 x Solder paddle | oiled | wide
- 1 x tinning paste SN97CU3
- 1 x bar tin - 25% lead content



## Bar tin | 25% lead content | 1000 g

Item no. 817010

Bar tin according to DIN EN 29453.  
Can be processed very well, retains its "pasty" state for a long time.

