

Spot weld remover for all vehicles

Convenient work even in hard-to-reach places thanks to simple, toolfree removal of the Variomatic handle. The 360° rotatable Variomatic handle prevents slipping and the depth stop prevents the underlying sheet metal from being damaged.

EFFORTLESS

PRECISE

CONTINUOUSLY ADJUSTABLE MILLING DEPTH

QUICK AND SIMPLE ASSEMBLY

WITH DEPTH STOP

FOR HIGH-STRENGTH AND **SUPER HIGH-STRENGTH MATERIALS**

VARIO DRILL WS90

Vario Drill WS90 with Variomatic

Item no. 601001

working area: 95 x 35 mm

Speed	Power	Vibration	Operating pressure	Weight
900 rpm	370 W	1.07 m/s ²	6-8 bar	1.8 kg

Scope of delivery:

- 1 × VARIO DRILL WS90
- 1 × Variomatic
- 1 × VARIANTIC milling cutter Ø 8 mm
- 1 × pin wrench
- 1 × transport case

Vario Drill WS90 with Jumbomatic

Item no. 601009

working area: 140 × 85 mm

Scope of delivery:

- 1 × VARIO DRILL WS90
- 1 × Jumbomatic
- 1 × VARIANTIC milling cutter Ø 8 mm
- 1 × pin wrench
- 1 x transport case



Vario Drill WS90 without Variomatic

Item no. 602001

Scope of delivery:

- 1 × VARIO DRILL WS90
- $1 \times VARIANTIC$ milling cutter Ø 8 mm
- 1 × pin wrench
- 1 x transport case



Vario Drill WS90

VarioDrill WS90 Clamps 608020 608018 Item no. 608019 Item Variomatic Jumbomatic Jumbomatic | Daimler version QTY / 1 pc. / 1 pc. / 1 pc. /







Crown Cutter Special

Item no. 607101

diameter: 14 mm

Scope of delivery:

1 x cutting head with mandrel

1 × spring + holding pin 3 × special crowns



Spare Crown

Item no. 607110

type N

diameter: 14 mm



Extensions for Vario Drill WS90				
Item no.	608012	608010	608011	
Item	VD 305	135 mm	85 mm	
Length	305 mm	135 mm	85 mm	
QTY/	1 pc. /	1 pc. /	1 pc. /	







Centering Attachments for Vario Drill WS90					
Item no.	608001	608002	627010		
Item	V1 I top side	V2 bottom side	drill bit NK-2F		
	only for solid carbide drill bits 627010	only for solid carbide drill bits 627010	3 cutting edges head-Ø: 6.7 mm shank-Ø: 8 mm total length: 49 mm		
QTY/	1 pc. /	1 pc. /	1 pc. /		
			for HCC LUHCC		







for the removal of self piercing rivets



BTR - Fluid

silicone free cutting oil

A silicone-free special oil that reduces friction during the cutting process and ensures a longer service life of the tool.

Item no.	648007	628000
Item	50 ml	125 ml
QTY/	1 pc. /	1 pc. /

